## IN THE CLAIMS

Please amend the claims as follows:

1. (original) A method of embedding a signature in an audiovisual signal for authentication of said audio-visual signal, said audio-visual signal being interlaced or non-interlaced, comprising the steps of

forming a signature based on a first portion of a frame of said audio-visual signal, and

embedding the signature in said first portion and/or at least a second portion of said frame of said audio-visual signal.

- 2. (original) A method according to claim 1, wherein said portions are patterns of consecutive horizontal lines of said audio-visual signal, said patterns having fewer lines than the entire audio-visual signal.
- 3. (original) A method according to claim 1, whereby said steps of forming and embedding are repeated until a signature has been embedded for all regions of said frame.

- 4. (currently amended) A method according to claim 1—or 2 whereby said first portion of said audio-visual signal is a first field comprising a slice of at least one consecutive line of said lines of said frame of said audio-visual signal and said second portion is a second field comprising a slice of at least one consecutive line of said lines of said frame of said audio-visual signal.
- 5. (original) A method according to claim 4 whereby said audiovisual signal is interlaced and said first field comprises all even or odd lines and said second field comprises all respectively remaining even or odd lines.
- 6. (currently amended) A method according to claims 1 or 2claim 1 whereby said audio-visual signal is non-interlaced and said portions being slices of at least one consecutive line of said lines of said audio-visual signal and said first portion and said slices comprising different consecutive lines of said audio-visual signal.
- 7. (currently amended) The method according to any preceding elaimclaim 1, the step of embedding the signature being characterised by embedding the signature as a watermark.

- 8. (original) The method according to claim 7 whereby the watermark is embedded as a spread spectrum watermark.
- 9. (original) The method according to claim 7, whereby the watermark is embedded in a different portion of said frame than the portion of said frame for which said signature is generated.
- 10. (original) The method according to claim 1 whereby the step of embedding the signature is further characterised by embedding the signature in a subsequent portion.
- 11. (original) The method according to claim 1 whereby the steps of forming and embedding said signature are performed in real-time.
- 12. (original) An apparatus for embedding a signature in an audio-visual signal for authentication of said audio-visual signal according to the method of claim 1, said apparatus comprising
- a means forming a signature based on a first portion of a frame of said audio-visual signal, and
- a means embedding said signature in said first portion and/or at least a second portion of said frame of said audio-visual signal.

- 13. (original) An apparatus according to claim 12, wherein said portions are patterns of horizontal lines of said audio-visual signal, said patterns having fewer lines than the entire audio-visual signal.
- 14. (original) A computer readable medium having a plurality of computer-executable instructions embedding a signature in an audio-visual signal for authentication of said audio-visual signal according to the method of claim 1 comprising
- a first program module forming a signature based on a first portion of a frame of said audio-visual signal, and
- a second program module embedding said signature in said first portion and/or at least a second portion of said frame of said audio-visual signal.
- 15. (original) A medium according to claim 14, wherein said portions are patterns of horizontal lines of said audio-visual signal, said patterns having fewer lines than the entire audio-visual signal.
- 16. (original) Use of the method according to claim 1 in a surveillance camera or security camera or digital image camera or digital video camera or a medical imaging system.